

AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application.

Listing of Claims

1. (Currently Amended) A framing system comprising:
 - a) a plank member having a front, generally flat, surface and an opposing back surface with at least one resilient rib protruding therefrom or at least one receptor pocket extending therein;
 - b) ~~a frame member at least two frame members of an underlying structure, wherein the frame members are spaced apart from one another and wherein each frame member has~~ having at least one receptor pocket extending therein or at least one resilient rib protruding therefrom, wherein the frame member rib or pocket is matable of each frame member engages with the ~~a plank member pocket or rib of the plank member;~~
 - c) wherein the at least one resilient rib has a profile with a first side and a second side which diverge from one another as they extend away from the member to which they are attached and converge to a tip at the furthestmost extension of the rib away from the member; and
 - d) ~~wherein the maximum height of a rib occurs at the place of maximum divergence; and~~
 - e) wherein the at least one rib has a maximum height and the at least one receptor pocket has a minimum width less than that of the maximum height of the rib such that ~~the rib may be~~ is captured within the receptor pocket.
2. (Previously Presented) The framing system according to claim 1, wherein plank member and the frame member are secured to one another through the engagement of the at least one resilient rib with the at least one receptor pocket.
3. (Cancelled).

4. (Previously Presented) The framing system according to claim 1, wherein the first side and the second side of the at least one resilient rib are spaced apart from one another as they extend away from the member and define a hollow interior therebetween .

5. (Original) The framing system according to claim 4, wherein the material of the at least one rib is capable of resilient bending.

6. (Previously Presented) The framing system according to claim 1, wherein the at least one rib is made of a resilient material that compresses for resiliency.

7. (Previously Presented) The framing system according to claim 6, wherein the rib is continuous between the first side and the second side to define a solid rib.

8. (Original) The framing system according to claim 2, wherein at least one receptor pocket has walls which are resilient.

9. (Original) The framing system according to claim 8, wherein the walls of the at least one receptor pocket are pushed apart to accommodate the rib.

10. (Original) The framing system according to claim 2, wherein one or both of the at least one rib and the at least one pocket receptor are barbed.

11. (Cancelled).

12. (Original) The framing system according to claim 1, wherein the at least one receptor pocket is within the frame member and wherein the at least one rib is within the plank member.

13. (Original) The framing system according to claim 12, wherein the at least one rib is a separate piece secured to the back surface of the plank member.

14. (Original) The framing system according to claim 1, wherein the at least one receptor pocket is in the plank member and the at least one rib is in the frame member.

15. (Original) The framing system according to claim 1, wherein each plank member interlocks with an adjacent plank member.

16. (Original) The framing system according to claim 1, wherein each of the plank members are overlapping with adjacent plank members.

17. (Cancelled).

18. (Cancelled).

19. (Cancelled).

20. (Cancelled)

21. (Withdrawn) A method of assembling a framing system having a plank member with a front, generally flat, surface and an opposing back surface with at least one rib protruding therefrom or at least one receptor pocket extending therein and having a frame member of an underlying structure with the other of at least one receptor pocket extending therein or at least one rib protruding therefrom, wherein the frame member rib or pocket is matable with the plank member pocket or rib comprising the steps of:

- a) aligning the at least one rib with the at least one receptor pocket;
- b) urging the at least one rib within the at least one receptor pocket until the rib snaps into the pocket; and

- c) wherein the at least one rib or the at least one receptor pocket is resilient.

22. (Withdrawn) A method of making a frame member adapted to receive protruding ribs from a plank member comprising the steps of:

- a) punching slots within a flat sheet; and
- b) bending the sheet into a structural member having a top surface and a bottom surface, wherein the slots extend within the top surface to provide a receptor pocket adapted to receive the protruding ribs from the plank member.